

# BRETFORD BASICS™ ADJUSTABLE AV CART

## A2642

Imagine, one cart that adjusts to meet all of your needs! Adjusting to multiple heights is as simple as resetting four screws. Open, roomy shelves provide ample storage space. Choice of black, cardinal, quartz, polo and topaz powder paint finish. Tops come with a rubber mat. Cart rolls easily on 4" casters.



## FEATURES

- Quickly and easily adjusts to five heights, from 26" to 42", for fast and easy changes by simply resetting four screws.
- Constructed from steel for strength and durability.
- Shelves have a 1/4" lip to keep equipment from sliding off and the top shelf includes a ribbed rubber mat.
- Durable shelves allow for storage of supplies and rounded edges provide extra safety.
- Ample room on top shelf accommodates CRT monitors up to 20" diagonal or virtually any audio visual equipment.
- 4" Quiet Glide casters (two lock) allow for easy movement and safety. Also available with 5" Quiet Glide casters.
- Optional 2-outlet or 3-outlet electrical unit with built-in cord winder and 20' extension cord lets you set up anywhere in the room and still reach an electrical outlet. Electrical units are standard on A2642E and A2642-M4.
- Optional Big Wheel Kit includes two non-swivel and two swivel-locking casters to increase mobility.
- Steel content contains an average of 30% post-consumer recycled steel.
- Black powder paint finish resists everyday wear and tear. Also available in four primary colors: Cardinal (-CD), Polo (-PL), Quartz (-QZ) and Topaz (-TZ).

## DIMENSIONS

Overall: 24" w x 18" d x 26-42" h

Shelf: 24" w x 18" d

Middle to bottom shelf: 15-1/2"

## COLOR & FINISH

Black (BK), Cardinal (CD), Polo (PL), Quartz (QZ) and Topaz (TZ)

## STANDARD EQUIPMENT

24" W x 18" D Shelves (3)

1" round plastic caster insert (4)

4" diameter casters (4)

18" x 24" Rubber Mat

Red plastic bag with all necessary hardware for assembly

2-outlet electrical unit (1) [A2642E only]

3-outlet electrical unit (1) [A2642-M4 only]

## WEIGHT AND FREIGHT CLASS

A2642: 40 lbs.

A2642E: 42 lbs.

A2642-M4: 42 lbs.

Freight class 85. Available to ship via UPS

Ships ready to assemble in one (1) carton pack



## ACCESSORIES

E-Unit Electrical assembly with 2 grounded outlets, 20 ft. grounded extension cord. UL listed when mounted on table. [Standard on A2642E.]

ES-Unit Electrical assembly with 3 grounded outlets, 20 ft. grounded extension cord. UL listed when mounted on table. [Standard on A2642-M4.]

044-0025 5" caster pak with 2 locking brakes.

044-0026 Big Wheel Kit

## 4" CASTER CARTS

### CARTON DIMENSIONS & UPC CODE

23-3/4" w x 20-3/4" d x 26-1/2" h

A2642: 0 96633 10003 3

A2642E: 0 96633 10004 0

A2642-M4: 0 96633 11077 3

## 5" CASTER CARTS

### CARTON DIMENSIONS & UPC CODE

23-3/4" w x 20-3/4" d x 26-1/2" h

A2642-P5: 0 96633 10762 9

A2642-E5: 0 96633 11076 6

A2642-M5: 0 96633 11078 0

## MADE IN THE USA

The A2642 adjustable cart is made at Bretford's Chicago area manufacturing facility using union labor.

## SUGGESTED SPECIFICATIONS

Adjustable Table has three (3) 20-gauge steel 18" x 24" shelves. Each shelf is press formed with a 1/4" lip bordering the top surface on all four sides. The top shelf has a 20-gauge steel stiffener electrically welded underneath the surface front to back. A Black rubber 18" x 24" mat is placed on the top shelf. The shelf has two (2) 3/16" diameter holes centered on both the right side and the left side to accept an optional electrical assembly. The table has an adjustable top section that consists of one (1) 20-gauge 18" x 24" shelf with four (4) 14-gauge steel legs 21-1/4" long welded to the shelf at each corner. Each offset leg has two (2) 1/4" diameter holes near the bottom of the section and in the center of the leg that will accept a 1/4-20 machine screw. The holes are spaced 4" apart to permit height adjustments of 26", 30", 34", 38" and 42" when matched to the bottom section of the table. Each offset leg fits over the bottom section of the table and is secured at the desired height by a machine screw. The bottom section of the adjustable table consists of two (2) 20-gauge steel 18" x 24" shelves - one at the top of the section and the other at the bottom. There are four (4) 14-gauge steel 19" legs welded to the shelves at each corner. Each 19" leg has four (4) 1/4" diameter holes down the center of the leg that will accept a 1/4-20 machine screw. Constructed using "prime" steel which has a 25% to 35% post-consumer recycled content. Holes are 4" apart to permit table height adjustments (as noted above). Model has a powder paint finish. A hard plastic caster insert is mounted to each leg. Casters are mar-resistant black hard rubber and 4" in diameter. Each caster assembly has ball bearing swivel capabilities and steel construction, two (2) have locking brakes. 4" stem casters are load rated for 115 lbs. each. Optional electrical assembly is completely enclosed with two (2) or three (3) grounded outlets. Includes 20 ft., 3-wire cord and two (2) 3/16" diameter machine screws with wing nuts for attaching unit to the table. Model A2642E comes standard with 2-outlet electrical assembly and A2642-M4 comes standard with 3-outlet electrical assembly. Equipment Table ships assembled in one (1) carton and is available to ship via UPS.



CARTS COME IN A VARIETY OF COLORS. SELECT THE ONE THAT BEST MATCHES YOUR SCHOOL COLORS OR ROOM COLORS.



11000 SEYMOUR AVENUE  
FRANKLIN PARK, ILLINOIS 60131 USA  
TOLL FREE PHONE 800-521-9614  
PHONE 847-678-2545  
TOLL FREE FAX 800-343-1779  
FAX 847-678-0852  
WWW.BRETFORD.COM