

BRETFORD BASICS™

UL LISTED FLAT PANEL WIDE BODY CART



FPBBUL32 Series FOR FLAT PANEL MONITORS TO 65 LBS

FPBBUL32 Flat Panel Carts have been certified to comply with UL standard 1667 for tall institutional carts.

For use with flat panel monitors not to exceed 65 lbs., 29.5 kg. Suggested use with 30" to 42" flat panel.



FEATURES

- Stability and load tested by Underwriter Laboratories for safe use with a flat panel monitor up to 65 lbs., 29.5 kg. in the United States and Canada. Any size monitor is appropriate as long as it does not exceed the maximum weight load, suggested for use with 30" to 42" flat panels.
- Universal mounting bracket is adjustable to fit the unique mounting hole pattern on the back of your monitor up to 700 mm wide by 400 mm tall, so there is no guess work on what monitor you can use. And you don't need a new cart just because you changed monitors.
- Monitor can be set at a 0°, 7-1/2° or 15° forward angle to reduce glare and provide the best angle for your audience.
- Integrated cord management keeps things neat and in their place and reduces the risk of snagging a cord during transport.
- A top shelf handle makes it easier to push the cart from one location to another by providing additional room to walk behind the cart.
- Wide body, pyramid design and sturdy steel construction lowers the center of gravity and provides superior stability.
- Top shelf includes a 22" monitor mounting pole and measure 32"w x 22"d. Top shelf is 44" off the floor.
- Middle shelf measures 32"w x 22"d (10-1/2" between top and middle shelves) and is ideal for use with a DVD and speakers.
- Bottom shelf measures 32"w x 27-1/2"d (23" between shelves) and works well with heavier equipment or as storage.
- Optional UL & C-UL listed 2-outlet electrical unit included with the FPBBUL32-E4BK and UL & C-UL listed 3-outlet electrical unit included with the FPBBUL32-M4BK. Both come with a 20 foot power cord and built-in cord winder.
- 4" industrial grade casters - two fixed and two swivel.
- Constructed using an average 30% post-consumer recycled steel content and finished in environmentally friendly Black powder paint. Steel and aluminum construction is 100% recyclable at the end of the product life cycle.



DIMENSIONS

Overall: 32" w x 27-1/2" d x 66" h (monitor not included in height)
Top and Middle Shelves: 32" w x 22" d
Bottom Shelf: 32" w x 27" d
Middle to Top Shelf: 10-1/2"
Bottom to Middle Shelf: 23-1/2"
Aluminum Mounting Pole: 22" l
Mounting Arm Plate: 31" w
Mount Arm Adjustability: 100-700mm wide x 100-400mm high
Forward Tilt Adjustment: 0°, 7-1/2°, 15°

COLOR & FINISH

Black (-BK) powder paint

STANDARD EQUIPMENT

- (2) 32" w x 22" d Shelves
- (1) 32" w x 27" d Bottom Shelf
- (1) Top Shelf Handle
- (1) 22" l Aluminum Mounting Pole
- (2) Monitor Mounting Arms
- (1) Monitor Arm Mounting Plate
- (1) Angle Adjustable Mounting Box
- (1) Aluminum Mounting Nugget
- (4) 4" Casters, (2) Fixed and (2) Swivel
- (1) Red Plastic Bag with Hardware for Assembly
- (1) 2-Outlet Electrical Assembly (FPBBUL32-E4BK only)
- (1) 3-Outlet Electrical Assembly (FPBBUL32-M4BK only)

WEIGHT AND FREIGHT CLASS

FPBBUL32-P4BK: 86 lbs., Freight class 70 UPS
FPBBUL32-E4BK: 89 lbs., Freight class 70 UPS
FPBBUL32-M4BK: 89 lbs., Freight class 70 UPS



All models ship ready-to-assemble in one (1) carton pack and are available to ship LTL truck or via UPS.

CARTON DIMENSIONS & UPC CODE

FPBBUL32-P4BK: 0 96633 30778 4
FPBBUL32-E4BK: 0 96633 30779 1
FPBBUL32-M4BK: 0 96633 30780 7
Carton Pack: 46" w x 31" d x 7" h, 5.78 cubes



Tilt Adjustment



Easy to Use Handle

SAFETY RATING SPECIFICATIONS

FPBBUL32 Flat Panel Wide Body Carts have been tested by Underwriter Laboratories and certified to comply with UL standard 1667 for tall institutional carts and is designated for use with flat panel monitors up to 65 lbs., 29.5 kg. Certified for the United States and Canadian markets.

ELECTRICAL UNIT SPECIFICATIONS

Optional electrical assembly is completely enclosed in a steel case with two (2) or three (3) grounded outlets, 20 ft. 3-wire power cord, cord winder, and two (2) 3/16" diameter machine screws with wing nuts. Units attach to pre-drilled holes in the top or middle shelf and are UL listed when attached to the FPBBUL32 cart. Electrical units are included as standard on model FPBBUL32-E4BK (2-outlet electrical unit) and model FPBBUL32-M4BK (3-outlet electrical unit.)

MONITOR MOUNTING SPECIFICATIONS

The monitor assembly has two arms that secure to the mounting holes in the back of the monitor and hang on a horizontal plate that secures to the aluminum pole. Arms are adjustable to fit the mounting hole pattern on the back of the monitor from 100 mm to 700 mm wide and 100 mm to 400 mm high. A transition plate has forward tilt adjustment settings of 0°, 7-1/2° or 15° and is designed to prevent slipping of the monitor's angle when in transit.

CART ASSEMBLY SPECIFICATIONS

FPBBUL32 carts include two (2) 18-gauge steel 32" w x 22" d shelves and one (1) 18-gauge 32" w x 27-1/2" d bottom shelf. Shelves are press formed with a 1/8" lip bordering the top surface on all four (4) sides to help prevent materials from sliding off. Legs fit flush to the shelves and interlock with mounting brackets for added strength. Each corner has 13-gauge steel mounting brackets with 1/4" square head bolts and hex nuts that tighten to hold leg securely to the shelf. The two (2) 32" w x 22" d shelves have two (2) 3/16" diameter holes centered on both the right and the left side to accept an optional electrical assembly. Top shelf has reinforced plating on the underside and mounting holes for an aluminum pole and supports a handle for pushing the cart. Aluminum mounting pole is 22" l and allows a flat panel monitor to be mounted to the front side, the back side includes mounting stops. The front and rear of the pole include a cord management channel. Legs are 18-gauge 1" square tubular steel. Each leg is 39-1/2" in length and tapered so the top section fastens to two 32" w x 22" d shelves and the bottom fastens to a 32" w x 27-1/2" d base shelf. The cart stands 66" h (not including the monitor), top shelf is 44" h. Casters are mar resistant hard black rubber and measure 4" in diameter. Two (2) casters are fixed and two (2) swivel. Carts are constructed using "prime" steel which has a 25% to 35% post-consumer recycled content and finished in a durable and environmentally friendly Black Pumice powder paint. All carts ships knocked down (KD) in one carton pack and are available to ship via LTL truck or United Parcel Service (UPS).



BRETTFORD

11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM