

BRETFORD BASICS™

PRE-ASSEMBLED NOTEBOOK STORAGE CART

LAPTG15SA-GM & LAPTG15ESA-GM

Bretford's 16 laptop carts ship pre-assembled from the factory and stores and charges up to 16 computers. All steel construction with locking doors and padlock deters theft and helps ensure the security of equipment. Finished in Grey Mist powder paint.



FEATURES

- Welded and ships fully assembled from the factory, simply uncrate and use.
- LAPTG15SA-GM does not include any electrical components.
- LAPTG15ESA-GM includes 15-outlet, UL listed, overload protected, electrical panel to charge laptops. Electrical panel is accessed by a rear door, door is secured with a combination padlock.
- Cart features two shelves with eight compartments per shelf for up to 16 laptops, shelf dividers may be removed for storing larger items.
- Top shelf can be used as a space for laptop and printer or as a general working surface.
- Individual cord holders for each laptop provide convenient cord management.
- Solid steel construction and locking doors ensure security of equipment.
- Doors lock with a Bretford re-settable combination lock, two locks included.
- Single grommet hole in back of unit enables electrical unit to be plugged into wall for easy charging of laptops.
- 5" casters, two lock, allow cart to be rolled easily from room to room.
- Features ventilation holes in the back panel to cool equipment when charging.
- * Cart is constructed using 30% post-consumer recycled steel.

DIMENSIONS

Overall: 35-1/2"w x 21-1/2"d x 38-1/8"h

Compartments: 4-3/16"w x 15-1/2"d x 13-1/2"h

COLOR & FINISH

Grey Mist (-GM) powder paint

STANDARD EQUIPMENT

33-1/2"w x 21-1/2"d Top Shelf

33-1/2"w x 19-1/2"d Bottom Shelf

33-1/2"w x 19"d Interior Shelf

Steel Divider Panels (14)

Non Slip Rubber Shelf Mats (3)

Back Door Panel

Front Doors Panels (2)

15 Outlet Electrical Panel (1) [LAPTG15ESA-GM Only]

5" Plate Casters (4)

Built In Handle (2)

Three Dial Combination Padlocks (2)

WEIGHT AND FREIGHT CLASS

LAPTG15SA-GM: 139 lbs., Freight class 125

LAPTG15ESA-GM: 154 lbs., Freight class 125

Ships pre-assembled in one (1) carton pack

CARTON DIMENSIONS & UPC CODE

Carton: 40"w x 26"d x 42-1/2"h

LAPTG15SA-GM: 0 96633 24847 6

LAPTG15ESA-GM: 0 96633 22587 3

SUGGESTED SPECIFICATIONS

Notebook Storage Cart shall come fully assembled and have one (1) 33-1/2"w x 22-1/2"d, 18-gauge steel work surface shelf which shall have one (1) 2" diameter grommet hole in rear of shelf to feed cords to electrical units. Cart shall also have one (1) 33-1/2"w x 21-1/2"d, 18-gauge steel bottom shelf, and one (1) 33-1/2"w x 19-1/2"d middle shelf. Middle shelf includes a welded 14-gauge steel lock bracket that protrudes through the front doors and secures using a padlock. Bottom and middle shelves can be divided with up to seven (7) divider shelves that create up to eight 4-3/16"w x 15-1/2"d x 13-1/2"h computer compartments per shelf. Dividers may be removed for larger equipment. Dividers are 18-gauge steel. Top shelf shall be covered with a black rubber mat so equipment does not slide and bottom and middle shelves shall be also be covered with a black rubber mat cut to accommodate divider shelves. Cabinet structure comes pre-assembled and consists of a pre-welded 18-gauge, 1" square tubing frame, 20-gauge pre-welded steel side panels, and a 20-gauge pre-welded back panel. Two 20-gauge steel doors mount to the front of the cabinet and secure using a re-programmable, three-dial combination padlock. Rear access door is 20-gauge steel and perforated to ventilate equipment. Rear door secures using a re-programmable, three-dial combination padlock. Back panel has one (1) 2" diameter grommet hole located at the bottom rear for cord management. LAPTG15ESA-GM shall have one (1) UL listed, fifteen

(15) outlet electrical panel which shall be attach inside the upper back of the cabinet and is accessed by the back door panel. Unit has four (4) 5" stem casters, two with locking brakes. Cart shall have two (2) integrated push handles to easily move cart from one location to another. Each model painted in grey powder coated paint and is constructed from "prime" steel which contains 25% to 35% post-consumer recycled content. Ships assembled by truck only.

ELECTRICAL UNIT SPECIFICATIONS

Electrical panel on the LAPTG15ESA-GM is attached to the upper back section of the cabinet and is accessed by the rear door. Unit is UL listed, overload protected, includes a 20' power cord, and has an on/off switch located on the side. The electrical unit is rated for a maximum of 15 amps usage, however, to prevent nuisance tripping of the breaker you should not exceed 13 amps of usage for an extended period of time,



THE BACK OF THE UNIT OPENS FOR EASY ACCESS TO THE ELECTRICAL UNIT.



THE RE-SETTABLE COMBINATION PADLOCK SLIPS THROUGH A TOUNGE THAT FITS THROUGH THE DOOR.



11000 SEYMOUR AVENUE
FRANKLIN PARK, ILLINOIS 60131 USA
TOLL FREE PHONE 800-521-9614
PHONE 847-678-2545
TOLL FREE FAX 800-343-1779
FAX 847-678-0852
WWW.BRETTFORD.COM